



## Redus Universal Universal-Getriebefett

### Beschreibung

Universalfett ist für Getriebe und innenliegende bewegliche Teile von Elektrowerkzeugen, Gartengeräten und anderen Mechanismen bestimmt, Geräte, die bei hohen Belastungen und Temperaturen arbeiten.

Durch die EP-Klasse schmier Additive effektiv die Oberfläche, bieten hohe Verschleiß-

und Korrosionsschutzeigenschaften. Bietet langfristigen Schutz vor Wasserauswaschung und Überhitzung von beweglichen Teilen.

Jede Tube ist mit einem abnehmbaren "Nasenapplikator" für eine bequeme Anwendung ausgestattet.

### Containertypen

Tube 100g

### Vorteile

- Reduziert den Verschleiß bei hohen Temperaturen und Vibrationen;
- Mechanische und antioxidative Stabilität;
- Ausgezeichnete Schmierung und geringe Verdampfung;
- Schutz vor Rost und Korrosion;
- Beständigkeit gegen Wasserauswaschung.

### Erfüllt Spezifikationen

NLGI 1 | EP | DIN 51502: K3K-40 | ISO 6743-9: L-XDCHA3 |

### Typische Kennwerte

Efficient viscosity at -20 °C, Pa • s-1, not more than	600
Penetration at 25°C, mm•10-1	310-340
Dropping Point, °C	180
Corrosion impact	stands
Colloid stability, %	18
Evaporation, not more than	2
Welding load, N, min	2450

#### Temperaturbereich



Produced according to TC U 20.5-31852954-100:2018. This information is a reference and can be changed without notice.