JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



Redus Universal

Universal-Getriebefett

Beschreibung

Universalfett ist für Getriebe u nd innenliegende b ewegliche Teile von Elektrowerkzeugen, Gartengeräten u nd anderen Mechanismen b estimmt, Geräte, die b ei hohen Belastungen u nd Temperaturen arbeiten.
Durch die EP-Klasse schmieren Additive effektiv die Oberfläche, bieten hohe Verschleiß-
und Korrosionsschutzeigenschaften. Bietet langfristigen Schutz vor Wasserauswaschung u nd Überhitzung von b eweglichen Teilen.
Jede Tube ist mit einem abnehmbaren“ Nasenapplikator“ für eine b equeme Anwendung ausgestattet.

Containertypen

- Tube 100g

Vorteile

- Reduziert den Verschleiß bei hohen Temperaturen und Vibrationen;
- Mechanische und antioxidative Stabilität;
- Ausgezeichnete Schmierung und geringe Verdampfung;
- Schutz vor Rost und Korrosion;
- Beständigkeit gegen Wasserauswaschung.

Erfüllt Spezifikationen

NLGI 1 | EP | DIN 51502: K3K-40 | ISO 6743-9: L-XDCHA3 |

Typische Kennwerte

Efficient viscosity at -20 °C, Pa • s-1, not more then	600
Penetration at 25°C, mm•10–1	310-340
Dropping Point, ˚C	180
Corrosion impact	stands
Colloid stability, %	18
Evaporation, not more then	2
Welding load, N, min	2450

Temperaturbereich

-40˚C 0 ˚C +130˚C

Produced according to TC U 20.5-31852954-100:2018. This information is a reference and can be changed without notice.