YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



CVL IND SP

YUKO 1-13 (NLGI 3/4)

Universelles Gleitfett.

Beschreibung

Wird für die Schmierung verschiedener Wälzlager verwendet, seltener - Gleitlager, Motorlager, Radnaben von Altfahrzeugen.
Die Fettlebensdauer in Lagern ist ausreichend lang. In den Lagern der Elektromotoren sollten sie alle drei Jahre ausgetauscht werden. Die Fettzufuhr zu den Reibungseinheiten erfolgt sowohl über Druckpistolen als auch durch manuelle befüllung.

Containertypen

Tin bucket 17,0kg

Barrel 170kg

Vorteile

- Ausgewogene Formel und hohe Qualität der Rohstoffe;
- Lange Lebensdauer der Lager;
- Verbesserte Pumpfähigkeit bei niedrigen Temperaturen.

Erfüllt Spezifikationen

NLGI 3/4 |

Typische Kennwerte

Effective viscosity at 0°C	350
Shear strength at 80°C	200
Dropping point, °C, min	140
Colloid stability, %	10
Volatibility at 100°C per 1h	1.6
Penetration at 25°C with mixing, mm×10-1	220

Temperaturbereich

-20˚C 0 ˚C +100˚C

Produced according to TU U 20.5-31852954-062:2014. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.