YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



PVL

YUKO CLASSIC 15W-40

Universelles Ganzjahres-Mineralöl.

Beschreibung

Bestimmt für Benzin- und Dieselmotoren von Pkw, Transportern u nd leichten Nutzfahrzeugen nach Herstellerangaben.
Hergestellt aus hochwertigen mineralischen Grundölen mit modernem Additivpaket für einen einwandfreien Betrieb des Motors.

Containertypen

Canister 1L | Canister 4L | Canister 5L | Tin bucket 20L | Barrel 200L | In bulk

Vorteile

- Oil flexibility allows to use it for all gasoline and diesel engines of passenger cars manufactured before 2001;
- Optimal für die zuvor gefertigten “VAZ"; „GAZ"; Personenwagen;
- Kompatibel mit allen Motordichtungen;
- Eine breite Palette von Verpackungen erfüllt die Anforderungen aller Geräte;

Erfüllt Spezifikationen

SAE 15W-40 | API SF/CC |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	14.5
Density at 20˚C, kg/m³	890
Viscosity index	120
Alkalinity, mg KOH/g	5.3
Flash point in open crucible, ˚C	220
Pour point, ˚C	-25

Temperaturbereich

-22˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-008-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.