YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



PVL

YUKO DYNAMIC 10W-40

Universelles Motoröl mit hohem Anteil an synthetischen Komponenten.

Beschreibung

Bestimmt für Benzin- und Dieselmotoren von Pkw, Transportern u nd leichten Nutzfahrzeugen nach Herstellerangaben.

Hergestellt aus hochwertigen Grundölen mit verbessertem Additivpaket mit synthetischen Komponenten, die eine hohe Leistung b ieten.

Containertypen

Canister 1L | Canister 4L | Canister 5L | Tin bucket 20L | Barrel 200L

Vorteile

- Guter Verschleißschutz, antioxidative und dispergierende Eigenschaften;
- Erhöhte Motorsauberkeit durch den hohen Anteil an synthetischen Komponenten;
- Einfacher Kaltstart im Winter;
- Eine breite Palette von Verpackungen erfüllt die Anforderungen aller Geräte.

Erfüllt Spezifikationen

SAE 10W-40 | API SF/CC |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	14,3
Density at 20˚C, kg/m³	885
Viscosity index	138
Alkalinity, mg KOH/g	5.1
Flash point in open crucible, ˚C	210
Pour point, ˚C	-32

Temperaturbereich

-29˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-045:2010. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.