YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND

YUKO EOM-1 (ISO 32)

Wasserlösliches, schmierendes Kühlmittel.

Beschreibung

Emulsol, verwendet in Form einer 5%igen Emulsion. Bestimmt für den Einsatz b eim Schärfen, Fräsen, Bohren, Reiben, Formen, Gewindeschneiden, Räumen, Schleifen von Gusseisen, Kohlenstoff, niedrig- und mittellegierten Baustahl, einigen Legierungen u nd NE-Metallen.

Containertypen

Canister 17,5kg

Barrel 180kg

In bulk

Vorteile

- Eine hohe Biostabilität;
- Verbesserte Effizienz und Haltbarkeit;
- Fehlen von Schwermetallen;
- Sicher für die Umwelt und die menschliche Gesundheit;
- Gute Benetzungs- und Reinigungseigenschaften;
- Verbesserte Behandlungsqualität und reduzierter Geräteverschleiß;
- Ausgezeichneter Korrosionsschutz.

Erfüllt Spezifikationen

ISO 32 |

Typische Kennwerte

Kinematic viscosity at 50 °C, mm/s	39,5
Density at 20 °C, kg/m	880
Corrosive effect on metals	stands
pH value of 5% operation emulsion, pH units	9.9

Temperaturbereich

+15˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-023:2005. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.