# Produktdatenblat
# Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com




IND SP

# YUKO ESh

## Öl für hydraulische Steuerungen von hochbelasteten Maschinen.

## Beschreibung

Bestimmt für hydraulische Steuerungen von schwer b eladenen Maschinen ( Schreitbagger u nd ähnliche Maschinen).
Hergestellt aus hochwertigen Grundölen mit effektiven Additiven.

## Containertypen

Canister 20L

Barrel 200L

In bulk

## Vorteile

- Schützt hydraulische Getriebekomponenten vor Korrosion;
- Gute Filtrierbarkeit und Antischaumeigenschaften;
- Bietet die Stabilität der Viskositäts-Temperatur-Eigenschaften über den gesamten Betriebstemperaturbereich;
- Gute Dispergiereigenschaften und chemische Stabilität verhindern Ablagerungen und Lackbildung auf den Oberflächen von Hydrauliksystemkomponenten;
- Minimiert den Verschleiß der Reibelemente über die gesamte Lebensdauer;
- Kompatibel mit allen Gummidichtungen im Hydrauliksystem.

## Erfüllt Spezifikationen

**ISO 32 | ISO HH |**

## Typische Kennwerte

| | |
|---|---|
| Kinematic viscosity at 50˚C, mm²/s | 23 |
| Viscosity index | 137 |
| Density at 20˚C, kg/m³ | 878 |
| Acid index, mg KOH/g | 0.05 |
| Flash point in open crucible, ˚C | 170 |
| Pour point, ˚C | -50 |

**Temperaturbereich**

-47˚C 0 ˚C +45˚C

Produced according to GOST 10363-78. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.