YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND SP

YUKO FORMA 68 (ISO 68)

Formschmierendes Fluid.

Beschreibung

Wird zur Schmierung von Metallgehäusen u nd - formen b ei der Herstellung von Leichtbetonprodukten (Porenbeton, Schaumbeton u nd Gasbeton) eingesetzt.

Das Produkt muss nicht vorgemischt werden. Es wird gebrauchsfertig geliefert.

Containertypen

Canister 17,5kg

Barrel 180kg

In bulk

Vorteile

- Ermöglicht die Herstellung einer sauberen Gussoberfläche, ohne Flecken und Bleichbeton;
- Verlängert die Lebensdauer von mit Holz oder Kunststoff beschichteten Formen;
- Verhindert die Korrosion von Metallformen;

Erfüllt Spezifikationen

ISO 68 |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s		68.0
Total base	, mg KOH/g	6.5
Flash point in open crucible, ˚C		220
Pour point, ˚C		-15

Temperaturbereich

-10˚C 0 ˚C +50˚C

Produced according to TU U 19.2-31852954-055:2013. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product