YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND SP

YUKO FORMA 8 (ISO 7)

Formschmierendes Fluid.

Beschreibung

Wird zur Schmierung von Betonschalungen b ei der Herstellung von Stahlbeton-, Beton-
und Schaumbetonprodukten sowie für verschiedene Formen u nd Schalungen im Bauwesen verwendet.
Das Produkt muss nicht vorgemischt werden. Es wird gebrauchsfertig geliefert.

Containertypen

Canister 17,5kg

Barrel 175kg

In bulk

Vorteile

- Einfache Trennung der Form von den Produkten auch nach mehreren Tagen;
- Reinigen Sie die Produktoberfläche, ohne Flecken;
- Nach der Verwendung der Flüssigkeit ist keine zusätzliche Reinigung der Form erforderlich;
- Korrodiert keine Metallformen;
- Effizienter Verbrauch;
- Hohe biologische Abbaubarkeit.

Erfüllt Spezifikationen

ISO 7 |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s		8.0
Total base	, mg KOH/g	9.1
Flash point, ˚C		165
Pour point, ˚C		-15

Temperaturbereich

-10˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-040:2008. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.