YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND SP

YUKO FORMA 9 (ISO 10)

Formschmierendes Fluid.

Beschreibung

Wird zur Schmierung von Betonschalungen b ei der Herstellung von Stahlbeton-, Beton-
und Schaumbetonprodukten sowie für die Vielfalt der Schalungen u nd Schalungen im Bauwesen eingesetzt.
Das Produkt muss nicht vorgemischt werden. Es wird gebrauchsfertig geliefert.

Containertypen

Canister 17,5kg

Barrel 180kg

In bulk

Vorteile

- Einfache Trennung der Form von den Produkten auch nach mehreren Tagen;
- Reinigen Sie die Produktoberfläche, ohne Flecken;
- Nach der Verwendung der Flüssigkeit ist keine zusätzliche Reinigung der Form erforderlich;
- Korrodiert keine Metallformen; ;
- Effizienter Verbrauch.

Erfüllt Spezifikationen

ISO 10 |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s		9.0
Total base	, mg KOH/g	6,8
Flash point, ˚C		152
Pour point, ˚C		-16

Temperaturbereich

-10˚C 0 ˚C +50˚C

Produced according to TU U 23.2-31852954-040:2008. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.