YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



SP

YUKO FORMULA 15W-40

Extraklassenmineralmotoröl.

Beschreibung

Bestimmt für den ganzjährigen Einsatz in Benzin- und Dieselmotoren von Pkw u nd Transportern, inkl. Injektor, Multiventil, Turboaufladung.

Hergestellt aus hochwertigen mineralischen Grundölen mit ausgewogenem Additivpaket.

Containertypen

Tin bucket 20L | Canister 20L | Barrel 200L | In bulk

Vorteile

- Ideales Preis-Leistungs-Verhältnis;
- Die Universalität des Öls erlaubt es, es in fast allen Benzin- und Dieselmotoren von Autos, die vor 2003 hergestellt wurden, zu verwenden; ;
- Hat einen guten Schaum- und Korrosionsschutz;
- Kompatibel mit allen Dichtungsmaterialien;
- Keine Hoch- und Tieftemperaturablagerungen im Motor;
- Hat eine gute Reinigungskraft, die eine effektive Ablagerung und Schlammabfuhr aus dem Motor ermöglicht.

Erfüllt Spezifikationen

SAE 15W-40 | API SJ/CF-4 |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	14,75
Viscosity index	126
Alkalinity, mg KOH/g	9,9
Flash point in open crucible, ˚C	220
Pour point, ˚C	-30

Temperaturbereich

-26˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-008-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.