Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



CVL SP

YUKO Graphite Grease

Universelles Fett auf Kalziumbasis.

Beschreibung

Zum Schmieren von hochbelasteten Gleitreibungseinheiten von niedertourigen Mechanismen, Federn, Traktor- und Maschinenaufhängungen, Wagenhebern, offenen Getrieben u sw.
Hergestellt aus einer mittelviskosen Erdölmischung, verdickt mit wasserhaltigen Fettsäuren, Kalziumseife pflanzlichen u nd tierischen Ursprungs, mit Graphitzusatz als Festschmierstoff.

Containertypen

Doypack	Tin 400g	Tin 800g	Plastic pail	Tin bucket	Barrel
0,375kg			9kg	17,0kg	170kg

Vorteile

- Guter Verschleißschutz und extreme Druckeigenschaften;
- Kann erfolgreich unter schwierigen Bedingungen eingesetzt werden;
- Optimaler Korrosionsschutz bei hohen Belastungen;
- Niedriger Reibungskoeffizient durch das Vorhandensein von festen Partikeln;
- Wasser- und Staubschutz;
- Entspricht GOST.

Erfüllt Spezifikationen

NLGI 2 |

Typische Kennwerte

Tensile strength at 20˚C, Pa	500
Dropping point, ˚C	90
Penetration at 25˚C, x10-1 mm	265
Colloid stability, %	4

Temperaturbereich

-20˚C 0 ˚C +70˚C

Produced according to GOST 3333-80. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.