Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



SP

YUKO GT-50 (ISO-22)

Hydrauliköl.

Beschreibung

Bestimmt für hydrodynamische Getriebe von Diesellokomotiven u nd Turbogetriebe von Dieselzügen.
Niedrigviskoses, hochreines Mineralöl mit Zusatzstoffen zur Verbesserung der Eigenschaften von Antioxidantien, Verschleißschutz, Korrosionsschutz u nd Schaumschutz.

Containertypen

Canister 20L

Barrel 200L

In bulk

Vorteile

- Gute Schmierfähigkeit;
- Hohe Oxidationsstabilität;
- Stabile Viskosität;
- Gute Verschleiß-, Korrosions- und Schaumdämpfungseigenschaften.

Erfüllt Spezifikationen

ISO 22 |

Typische Kennwerte

Kinematic viscosity at 50˚C, mm²/s	13.5
Viscosity index	90
Acid index, mg KOH/g	1.5
Flash point in open crucible, ˚C	180
Pour point, ˚C	-28

Temperaturbereich

-26˚C 0 ˚C +40˚C

Produced according to TU U 23.2-31852954-041-2008. This information is reference and it can be changed without a notice. This article is from 01/11/2015, it replaces all the early published descriptions of the product.