Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



SP

YUKO HYDROL HLP 32 ZF

Aschefreies Öl für Hydrauliksysteme.

Beschreibung

Aschefreies Hydrauliköl. Bestimmt für Hydrauliksysteme verschiedener Industrieanlagen (Maschine, Presse, etc.), mobile Hydrauliksysteme, die u nter verschiedenen Bedingungen b etrieben werden u nd Öle b enötigen, ohne Metallverunreinigungen, insbesondere Zink u nd Kalzium.

Containertypen

Canister 20L

Barrel 200L

In bulk

Vorteile

- Hohe thermische und hydrolytische Stabilität, Filtrierbarkeit;
- Reduziert den Verschleiß von Systemkomponenten durch hocheffiziente Verschleißschutzadditive;
- Reduziert das Risiko von Kavitationsschäden an Pumpen durch hervorragende Luftabgabe und Antischaumeigenschaften;
- Frei von Metallverunreinigungen, insbesondere Zink und Kalzium

Erfüllt Spezifikationen

ISO 32 | ISO 6743-4 (HM) | DIN 51524-2 (HLP) |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	28,8-35,2
Viscosity index	90
Density at 20˚C, kg/m³	880
Acid index, mg KOH/g max	0.2
Flash point in open crucible, ˚C	190
Pour point, ˚C	-35
Mass fraction of solids, %	doesn't contain
Mass fraction of zink, %	doesn't contain

Temperaturbereich

-32˚C 0 ˚C +45˚C

Produced according to TU U 19.2-31852954-075-2015. This information is reference and it can be changed without a notice.