YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



SP

YUKO HYDROL HLPD 68 ZF

Aschefreies Öl für Hydrauliksysteme.

Beschreibung

Aschefreies Hydrauliköl. Bestimmt für Hydrauliksysteme verschiedener Industrieausrüstungen (Maschine, Presse u sw.), mobile Hydrauliksysteme, die u nter schweren Lastbedingungen b etrieben werden u nd Öle erfordern, ohne Metallverunreinigungen, insbesondere Zink u nd Kalzium mit verbesserter viskothermischer Stabilität/;

Containertypen

Canister 20L

Barrel 200L

In bulk

Vorteile

- Hohe hydrolytische Stabilität, Filtrierbarkeit;
- Verbesserte visko-thermische Eigenschaften;
- Reduziert den Verschleiß von Systemkomponenten durch hocheffiziente Verschleißschutzadditive;
- Frei von Metallverunreinigungen, insbesondere Zink und Kalzium;
- Hat detergent-dispergierende Eigenschaften.

Erfüllt Spezifikationen

ISO 68 | ISO 6743-4 (HM) | DIN 51524-2 (HLPD) |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	61,2-74,8
Viscosity index	90
Density at 20˚C, kg/m³	890
Acid index, mg KOH/g max	0.2
Flash point in open crucible, ˚C	200
Pour point, ˚C	-25
Mass fraction of solids, %	doesn't contain
Mass fraction of zink, %	doesn't contain

Temperaturbereich

-22˚C 0 ˚C +45˚C

Produced according to TU U 19.2-31852954-075-2015. This information is reference and it can be changed without a notice.