YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



IND SP

YUKO HYDROL HM 100

Hochwertiges Hydrauliköl.

Beschreibung

Bestimmt für Hydrauliksysteme von Industrieanlagen sowie für Landwirtschafts-, Erdbewegungs-, Bau- und Geländeausrüstungen.

Hydrauliköl mit hohem Verschleißschutz u nd niedrigem Zinkgehalt, das den Einsatz in einer Vielzahl von Hydrauliksystemen von Industrie- und Mobilgeräten u nter schwierigen Betriebsbedingungen ermöglicht.

Containertypen

Canister 20L

Barrel 200L

In bulk

Vorteile

- Hohe Gebrauchseigenschaften;
- Hohe thermische und hydrolytische Stabilität;
- Ausgezeichnete hydrolytische Stabilität;
- Langfristige Oxidationsbeständigkeit;
- Schaumarm und gut filtrierbar;
- Kompatibilität mit Dichtungsmaterialien.

Erfüllt Spezifikationen

ISO 100 | ISO HM |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	95
Viscosity index	92
Density at 15˚C, kg/m³	880
Acid index, mg KOH/g max	0.65
Flash point in open crucible, ˚C	220
Pour point, ˚C	-25

Temperaturbereich

-22˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-017-2004. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.