YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



IND SP

YUKO HYDROL HM 15

Hochwertiges Hydrauliköl.

Beschreibung

Es wird in Antriebssystemen u nd hydraulischen Steuerungen eingesetzt, die u nter extrem schwierigen Bedingungen mit hohem Druck u nd hohen Temperaturen arbeiten.

Es b esteht aus hochwertigen mineralischen Grundölen mit einem ausgewogenen System von Additiven, die Antioxidantien, Verschleißschutz, Korrosionsschutz u nd Schaumschutz enthalten.

Die einzigartige Formel für die Herstellung von Hydrauliköl HM 15 sorgt dafür, dass es wesentlich länger wirkt als herkömmliche mineralische Hydrauliköle.

Containertypen

Canister 20L

Barrel 200L

In bulk

Vorteile

- Hohe thermische und hydrolytische Stabilität;
- Hohe Oxidationsbeständigkeit;
- Hohe Transferlast und Verschleißfestigkeit;
- ausgezeichnete Luftabgabe und Antischaumeigenschaften.

Erfüllt Spezifikationen

ISO 15 | ISO HM |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	14.7
Viscosity index	102
Density at 15˚C, kg/m³	871
Flash point in open crucible, ˚C	180
Pour point, ˚C	-25
Acid index, mg KOH/g max	0.65

Temperaturbereich

-23˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-017-2004. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.