YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



SP

YUKO HYDROL HM 32

Öl für Hydrauliksysteme.

Beschreibung

Bestimmt für Hydrauliksysteme verschiedener in- und ausländischer Geräte, die die hochwertigen, reinen Öle b enötigen. Hergestellt aus hochwertigen, hochreinen Grundölen mit Additivpaket.

Containertypen

Canister 20L

Barrel 200L

In bulk

Vorteile

- Verbessert die thermische und hydrolytische Stabilität und Filtrierbarkeit durch das Paket von Fremdadditiven;
- Reduziert den Verschleiß von Systemkomponenten durch hocheffiziente Verschleißschutzadditive;
- Verhindert Korrosion, reduziert negative Auswirkungen, die durch Wasser im System im Vergleich zu IGP-Ölen verursacht werden;
- Reduziert das Risiko von Kavitationsschäden an Pumpen durch hervorragende Luftabgabe und Antischaumeigenschaften.

Erfüllt Spezifikationen

ISO 32 | ISO HM |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	32
Viscosity index	98
Density at 15˚C, kg/m³	873
Acid index, mg KOH/g max	0.65
Flash point in open crucible, ˚C	205
Pour point, ˚C	-32

Temperaturbereich

-30˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-017-2004. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.