YUKO.UA

# Produktdatenblat
# Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM




IND

# YUKO HYDROL HM 46

## Hydrauliköl.

## Beschreibung

Bestimmt für Hydrauliksysteme verschiedener in- und ausländischer Geräte, die die hochwertigen, reinen Öle erfordern. Wird in der Ausrüstung mit Pumpen aller Art verwendet, die unter einem Druck von über 25MPa arbeiten.

Hergestellt aus hochwertigen, hochreinen Grundölen mit Additivpaket.

## Containertypen

Tin bucket 20L | Canister 20L | Barrel 200L | In bulk

## Vorteile

- Hochreine Reinheit bietet ein hohes Maß an Ölleistung;
- Hervorragende Tieftemperatur- und Korrosionsschutzeigenschaften;
- Hohe Oxidations- und Schaumbeständigkeit;
- Hoher Verschleißschutz in einem weiten Lastbereich.

## Erfüllt Spezifikationen

**ISO 46 | ISO HM |**

## Typische Kennwerte

| | |
|---|---|
| Kinematic viscosity at 40˚C, mm²/s | 45.5 |
| Density at 20˚C, kg/m³ | 890 |
| Viscosity index | 98 |
| Acid index, mg KOH/g | 0.65 |
| Flash point in open crucible, ˚C | 218 |
| Pour point, ˚C | -32 |

**Temperaturbereich**

-30˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-017-2004. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.