YUKO.UA

# Produktdatenblat
# Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM




IND SP

# YUKO HYDROL HV 100

## Hochwertiges Hydrauliköl.

## Beschreibung

Bestimmt für externe Hydraulikgeräte, die mit hohen thermischen u nd mechanischen Belastungen arbeiten, sowie für Industrie- und Automobilhydrauliksysteme, die über einen weiten Temperaturbereich arbeiten.

Hergestellt aus hochraffinierten Grundölen. Enthält ein ausgewogenes Additivpaket mit Antioxidantien, Verschleißschutz, Schaumschutz u nd Korrosionsschutz. Spezielle Additive b ieten einen hohen Viskositätsindex in einem weiten Bereich von Betriebs- und Umgebungstemperaturen.

## Containertypen

Barrel 200L

In bulk

## Vorteile

- Hohe antioxidative Stabilität;
- Hoher Viskositätsindex;
- Zuverlässiger Verschleißschutz;
- Hohe Demulgierfähigkeit und Antischaumeigenschaften;
- Rost- und Korrosionsschutz;
- Hervorragende thermische Stabilität.

## Erfüllt Spezifikationen

**ISO 100 | ISO HV |**

## Typische Kennwerte

| | |
|---|---|
| Kinematic viscosity at 40˚C, mm²/s | 95 |
| Viscosity index | 120 |
| Density at 15˚C, kg/m³ | 885 |
| Acid index, mg KOH/g | 0,65 |
| Flash point in open crucible, ˚C | 230 |
| Pour point, ˚C | -25 |

**Temperaturbereich**

-20˚C 0 ˚C +100˚C

Produced according to TU U 23.2-31852954-017-2004. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.