YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND SP

YUKO HYDROL HV 46

Öl für Hydrauliksysteme.

Beschreibung

Bestimmt für Hydrauliksysteme verschiedener in- und ausländischer Geräte, die die hochwertigen, reinen Öle b enötigen.

Containertypen

Barrel 200L

In bulk

Vorteile

- Großer Temperaturbereich für den Einsatz;
- Einfacher Kaltstart;
- Höchster Grad an Geräteschutz;
- Hervorragende Filtrierbarkeit unter nassen Bedingungen;
- Verlängerte Lebensdauer und verbesserte Beständigkeit gegen die für den harten Einsatz typischen Faktoren;
- Hervorragende Verschleißschutzeigenschaften, Oxidationsbeständigkeit und thermische Stabilität.

Erfüllt Spezifikationen

ISO 46 | ISO HV |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	46
Viscosity index	120
Density at 15˚C, kg/m³	875
Acid index, mg KOH/g max	0.65
Flash point in open crucible, ˚C	208
Pour point, ˚C	-39

Temperaturbereich

-35˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-017-2004. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.