YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



SP

YUKO HYDROL HV 68

Schmieröl für das Hydrauliksystem.

Beschreibung

Hochwertiges Hydrauliköl, bestimmt für Hochdruck-Hydrauliksysteme, die eine hohe Viskositätsstabilität für einen weiten Temperaturbereich erfordern. Entwickelt für hochbelastete Antriebssysteme, präzise hydraulische Steuerungssysteme, Hochdruck-Kolbenpumpen (konstanter oder variabler Durchfluss), Flügelzellenpumpen, die ein hohes Maß an Verschleißschutzöleigenschaften erfordern.

Containertypen

Barrel 200L

In bulk

Vorteile

- Hoher Viskositätsindex;
- Hohe Druckfestigkeit;
- Hoher Korrosionsschutz, hervorragende Entlüftung und Antischaumeigenschaften;
- Ausgezeichnete Filtrierbarkeit und Wasserbeständigkeit;
- Neutral gegenüber Dichtungsmaterialien.

Erfüllt Spezifikationen

ISO 68 | ISO HV |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	68
Viscosity index	120
Density at 15˚C, kg/m³	879
Acid index, mg KOH/g	0,65
Flash point in open crucible, ˚C	217
Pour point, ˚C	-39

Temperaturbereich

-35˚C 0 ˚C +80˚C

Produced according to TU U 23.2-31852954-017-2004. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.