YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND SP

YUKO I-50A

Industrieöl.

Beschreibung

Angewandt in Industriemaschinen, deren Betriebsbedingungen keine spezifischen Anforderungen an die Oxidations- und Korrosionsbeständigkeit von Ölen stellen, und als Hydraulikflüssigkeit. Diese Ölleistung ermöglicht den sicheren Einsatz zur Schmierung von niedrig- und mittel b elasteten Zahnradgetrieben, Gleitlagern u nd Gleitbahnen der Maschinen u nd vieler anderer Geräte, die den Einsatz der Spezialöle nicht erfordern.

Es ist ein lösungsmittelraffiniertes Grundöl ohne Zusatzstoffe.

*Gemäß GOST 20799-88 von April b is September darf der Stockpunkt nicht höher als minus 10˚C sein.

Containertypen

Barrel 200L

In bulk

Vorteile

- Hohe Oxidationsbeständigkeit;
- Gute demulgierende Eigenschaften.

Erfüllt Spezifikationen

ISO 100 | ISO HH |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	100.0
Density at 20˚C, kg/m³	882
Acid index, mg KOH/g	0.05
Flash point in open crucible, ˚C	240
Pour point*, ˚C	-15

Temperaturbereich

-10˚C 0 ˚C +45˚C

Produced according to GOST 20799-88. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.