Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



IND SP

YUKO INSp-65(ISO 100)

Öl für die Führungsbahnen.

Beschreibung

Wird zur Schmierung von niedrig- und mittel b elasteten horizontalen u nd vertikalen Führungen von Metallschneidemaschinen verwendet.

Hergestellt aus hochwertigen Grundölen mit Additiven.

Containertypen

Barrel 200L

In bulk

Vorteile

- Bietet hervorragenden Verschleiß- und Korrosionsschutz;
- Reduziert das Risiko von Fressen, Schlupf und Vibrationen unter den Bedingungen der Dünnfilm-Grenzschmierung;
- Ausgezeichnete Ölleistung sorgt für Sauberkeit von Maschinen und Anlagen, erforderliche Filtrierbarkeit, Trennbarkeit von Wasser und Kühlmitteln
- Reduziert die potenziellen negativen Auswirkungen von Kreuzkontaminationen, was die Lebensdauer von Schmierstoff und Kühlmittel verlängert.

Erfüllt Spezifikationen

ISO 100 |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	105,0
Viscosity index	90
Acid index, mg KOH/g	1,0
Flash point in open crucible, ˚C	220
Pour point, ˚C	-20

Temperaturbereich

-15˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-025:2005. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.