Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



IND

YUKO Kp-8C (ISO 46)

Kompressoröl.

Beschreibung

Wird zur Schmierung von Turbokompressoren in Verbindung mit hochbelasteten Getrieben verwendet.
Das Öl hat eine hohe Beständigkeit gegen Ablagerungen u nd eine gute Oxidationsstabilität.

Containertypen

Canister 20L

Barrel 200L

In bulk

Vorteile

- Hat eine bessere Oxidationsstabilität und verbesserte Korrosionsbeständigkeit im Vergleich zu anderen Turbinenölen;
- Die Möglichkeit des Einsatzes sowohl in offenen (druckbeaufschlagten) als auch in geschlossenen Schmiersystemen;
- In einigen Einzelgeräten ist er in der Lage, den ununterbrochenen Betrieb über 16. 000 Stunden und mehr zu gewährleisten;
- Es darf auch in Schraubenkompressoren verwendet werden, bei denen der Hersteller die Ölviskosität ISO 46 empfiehlt;
- Hohe Beständigkeit gegen Schlammbildung und gute Oxidation.

Erfüllt Spezifikationen

ISO 46 |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	46
Density at 20˚C, kg/m³	875
Viscosity index	98
Acid index, mg KOH/g	0.04
Ash content	0.004
Flash point in open crucible, ˚C	218
Pour point, ˚C	-15

Temperaturbereich

-13˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-007-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.