YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND

YUKO KS-19 (ISO 220)

Kompressoröl.

Beschreibung

Vorgesehen zur Schmierung von Mittel- und Hochdruck-Kolbenverdichtern. Wird in Kolben- und Rotationskompressoren mittlerer Beanspruchung (Mittel- und Hochdruck) bei Auslauftemperatur u nter 160 °C eingesetzt.

Containertypen

Canister 20L

Barrel 200L

In bulk

Vorteile

- Schützt die Geräte vor Verschleiß und Korrosion;
- Hat gute Leistungseigenschaften;
- Reduziert die Wartungskosten durch Zwangsausfälle;
- Zugelassen für den Einsatz bei den meisten Herstellern von Haushaltskolbenkompressoren.

Erfüllt Spezifikationen

ISO 220 |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	21,4
Viscosity index	88
Density at 20˚C, kg/m³	890
Flash point in open crucible, ˚C	262
Pour point, ˚C	-15

Temperaturbereich

-13˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-007-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.