Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



CVL

YUKO M-10DM

Saison-Motorenöl für Dieselmotoren.

Beschreibung

Zur Schmierung von leistungsstarken turboaufgeladenen Dieselmotoren (“MAZ"-LKWs, Lastzüge, Schlepper, Stadt- und Überlandbusse, Muldenkipper, Planierraupen, Schwerlastzugmaschinen) und mittelschweren Dieselmotoren mit moderater Aufladung oder natürlich angesaugt mit erhöhter Ölwechselzeit.
Hergestellt aus mineralischen Grundölen mit hochwertigen Additiven.

Containertypen

Canister 5L | OILBOX 20L | Tin bucket 20L | Canister 20L | Barrel 200L | In bulk

Vorteile

- Hohe Alkalität bietet eine ausgezeichnete Wasch- und Neutralisationsfähigkeit;
- Verbesserte Verschleiß- und Korrosionsschutzeigenschaften;
- Hohe thermisch-oxidative Stabilität;
- Gute Schaumbeständigkeit und ausgezeichnete Schmierfähigkeit;
- Sorgt für eine lange Ölablasszeit.

Erfüllt Spezifikationen

SAE 30 | API CD |

Typische Kennwerte

Kinematic viscosity at 100 ˚C, mm²/c	12.4
Density at 20 ˚C, kg/m³	892
Viscosity index	91
Base number, mg KOH/g	8.5
Flash point in open crucible, ˚C	236
Pour point, ˚C	-18

Temperaturbereich

-15˚C 0 ˚C +45˚C

Produced according to GOST 8581-78. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.