YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



CVL

YUKO M-10G2k

Saison-Motorenöl für Dieselmotoren .

Beschreibung

Einsetzbar in leistungsstarken Dieselmotoren, ohne Aufladung oder mit mäßiger Aufladung, sowie in schnelllaufenden stationären Dieselmotoren, Traktoren u nd Autos wie .

Hergestellt aus mineralischen Grundölen mit Additiven.

Containertypen

Canister 5L | OILBOX 20L | Tin bucket 20L | Canister 20L | Barrel 200L | In bulk

Vorteile

- Schützt Teile von Dieselmotoren vor allen Arten von Ablagerungen und Korrosion;
- Hat ausgezeichnete Schmiereigenschaften, hohe thermisch-oxidative Stabilität;
- Neutralisierende Säuren, die sich im Motorbetrieb bilden.

Erfüllt Spezifikationen

SAE 30 | API CC |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	11.16
Density at 20˚C, kg/m³	887
Viscosity index	90
Alkalinity, mg KOH/g	6.3
Flash point in open crucible, ˚C	230
Pour point, ˚C	-15

Temperaturbereich

-12˚C 0 ˚C +40˚C

Produced according to GOST 8581-78. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.