YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



CVL SP

YUKO M-14V2

Saisonöl für Diesellokomotiven- und Traktormotoren.

Beschreibung

Sie ist für mittelschwere Autotraktormotoren ohne Aufladung, Dieselgeneratoren, Pumpenaggregate, mittelgroße Diesellokomotiven b estimmt, die u nter erhöhter Belastung mit Dieselkraftstoff mit einem Schwefelgehalt von b is zu 0, 5% b etrieben werden.

Hergestellt aus mineralischen Grundölen mit Additiven.

Containertypen

Barrel 200L

In bulk

Vorteile

- Schützt Motorteile vor allen Arten von Ablagerungen und Korrosion;
- Hat gute Reinigungs-, Antioxidations-, Hochdruck- und Verschleißschutzeigenschaften;
- Neutralisierende Säuren, die sich im Motorbetrieb bilden.

Erfüllt Spezifikationen

SAE 40 | API CB |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	13.9
Density at 20˚C, kg/m³	900
Viscosity index	90
Alkalinity, mg KOH/g	5.8
Flash point in open crucible, ˚C	230
Pour point, ˚C	-12

Temperaturbereich

-12˚C 0 ˚C +45˚C

Produced according to GOST 12337-84. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.