Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



SP

YUKO M-6z/12G1

All-season motor oil based on mineral oil.

Beschreibung

Bestimmt für hochbelastete Benzinmotoren, die u nter schweren Bedingungen mit hoher thermischer Belastung u nd plötzlichem Wechsel der Betriebsarten b etrieben werden.

Hergestellt aus mineralischen Grundölen mit hochwertigen Additiven.

Containertypen

Canister 20kg | Tin bucket 20L | Barrel 200L | In bulk

Vorteile

- Bietet einen hervorragenden Schutz der Motoren gegen Schläge und Verschleiß;
- Ermöglicht den Kaltstart des Motors im Winter in einer gemäßigten Klimazone;
- Verhindert die Bildung von Kohlenstoff und Lack und minimiert den Verschleiß von Reibungsteilen;
- Hat eine hohe thermisch-oxidative Stabilität;
- Verhindert Korrosion beim Langzeitparken und Betreiben des Fahrzeugs.

Erfüllt Spezifikationen

SAE 15W-30 | API SF |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	14.1
Density at 20˚C, kg/m³	890
Viscosity index	118
Alkalinity, mg KOH/g	7.8
Flash point in open crucible, ˚C	220
Pour point, ˚C	-31

Temperaturbereich

-28˚C 0 ˚C +45˚C

Produced according to GOST 10541-78 This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.