YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



CVL SP

YUKO M-8DM

Winter Motoröl.

Beschreibung

Zur Schmierung von leistungsstarken turboaufgeladenen Dieselmotoren (Steinbruchkipper, Planierraupen, schwere Industrieschlepper, KAMAZ-Lkw, Straßenzüge, Traktoren, Busse u nd Reisebusse) und mittelschweren Dieselmotoren mit moderater Aufladung. Hergestellt aus b asischen Mineralölen u nd hochwertigen Additiven, die eine hervorragende Leistung b ieten.

Containertypen

Tin bucket 20L

Barrel 200L

In bulk

Vorteile

- Ausgezeichnete Wasch- und Neutralisationsfähigkeit;
- Zuverlässiger Schutz vor Ablagerungen;
- Verbesserte Verschleiß- und Korrosionsschutzeigenschaften;
- Hohe Wärme- und Oxidationsstabilität;
- Schaumbeständigkeit und ausgezeichnete Schmierfähigkeit;
- Dauerhafte Entleerungszeit.

Erfüllt Spezifikationen

SAE 20 W | API CD |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	8,3
Density at 20˚C, kg/m³	885
Viscosity index	97
Alkalinity, mg KOH/g	9,3
Flash point in open crucible, ˚C	215
Pour point, ˚C	-30

Temperaturbereich

-20˚C 0 ˚C +20˚C

Produced according to GOST 8581-78. This information is reference and it can be changed without a notice. This article is from 11/11/2015, it replaces all the early published descriptions of the product.