Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



CVL

YUKO M-8V

Ganzjahres-Motorenöl auf Mineralölbasis.

Beschreibung

Ganzjährig im Einsatz für mittelschwere Benzinmotoren von Pkw u nd Lkw sowie Winteröl für mittelschwere Motor- und Traktor-Dieselmotoren. Hergestellt aus mineralischen Grundölen mit speziellem Additivpaket. Es wird für den Einsatz in ZIL-, GAZ- und UAZ-Fahrzeugen mit zulässigen Entleerungsintervallen b is zu 18 000 km empfohlen.

Containertypen

Canister 5L | Canister 20L | Barrel 200L | In bulk

Vorteile

- Ermöglicht den Kaltstart des Motors im Winter in einer gemäßigten Klimazone;
- Verhindert Lack- und Kohlenstoffbildung, minimiert den Verschleiß von Reibungsteilen;
- Hat eine hohe thermisch-oxidative Stabilität;
- Verhindert Korrosion während des Betriebs oder des Langzeitparkens des Fahrzeugs.

Erfüllt Spezifikationen

SAE 20 | API SD/CB |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	8.1
Density at 20˚C, kg/m³	885
Viscosity index	98
Alkalinity, mg KOH/g	4.5
Flash point in open crucible, ˚C	220
Pour point, ˚C	-25

Temperaturbereich

-20˚C 0 ˚C +40˚C

Produced according to GOST 10541-78. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.