YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



CVL SP

YUKO Mark P (ISO 22)

Hydrauliköl.

Beschreibung

Bestimmt für Servolenkungen u nd hydrostatische Getriebe, Automatikgetriebe sowie hydraulische Anbaugeräte u nd Drehmomentwandler. Bietet dauerhaften Schutz von Materialien u nd Beschichtungen über die gesamte Lebensdauer des Hydrauliksystems.
Hydrauliköl der Marke P - ist ein hochreines Destillatöl mit effizienten Additiven.

Containertypen

Canister 20L

Barrel 200L

In bulk

Vorteile

- Hohe thermische Oxidationsstabilität;
- Bietet dauerhaften Schutz von Materialien und Beschichtungen des Hydrauliksystems;
- Gute Antischaum-, Verschleiß- und Dispersionseigenschaften.

Erfüllt Spezifikationen

ISO 22 |

Typische Kennwerte

Kinematic viscosity at 50˚C, mm²/s	7.0
Density at 20˚C, kg/m³	895
Viscosity index	90
Flash point in open crucible, ˚C	125
Pour point, ˚C	-30

Temperaturbereich

-27˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-003-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.