Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



YUKO MEGA HD 10W-40

Ganzjahres-Motorenöl für moderne Dieselmotoren.

Beschreibung

Ganzjahres-Motorenöl für Schwerlast-Dieselmotoren (einschließlich Turboaufladung mit AGR u nd OMS) von Landwirtschafts-, Bau-, Bergbaufahrzeugen u nd Lastkraftwagen.

Containertypen

Canister 20L

Barrel 200L

In bulk

Vorteile

- Einfacher Start im Winter;
- Hohe und stabile Leistung unter allen Betriebsbedingungen;
- Ausgezeichnete Antischaumfähigkeiten;
- Es verhindert die Bildung von Hoch- und Tieftemperaturablagerungen;
- Kompatibel mit den Dichtungen.

Erfüllt Spezifikationen

SAE 10W-40 | API CI-4 | MB 228.5, MAN M 3277, VOLVO VDS-3, RENAULT RXD/RLD-2, SCANIA LDF-2/LDF-3, MTU TYPE 3, IVECO |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	14,1
Density at 20˚C, kg/m³	861,6
Viscosity index	147
Alkalinity, mg KOH/g	10,9
Flash point in open crucible, ˚C	226
Pour point, ˚C	-30

Temperaturbereich

-27˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-079:2016. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.