YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



SP

YUKO MEGA 15W-40

Ganzjähriges Mineral-Motorenöl einer neuen Generation.

Beschreibung

Ganzjährig in Benzin- und Diesel-Verbrennungsmotoren (Saug- und Turbomotoren) von Pkw, Transportern und leichten Nutzfahrzeugen der neuesten Modelle eingesetzt.
Hergestellt aus hochwertigen mineralischen Grundölen mit ausgewähltem Additivpaket.

Containertypen

Canister 5L | Tin bucket 20L | Canister 20L | Barrel 200L | In bulk

Vorteile

- Gleichbleibend hohe Leistung in verschiedenen Betriebsarten;
- Einfacher Motorstart bei niedriger Umgebungstemperatur;
- Bietet einen reduzierten Ölverbrennungsverlust;
- Stabilität der Viskositätsbewertung innerhalb der Viskositätsklasse über die gesamte Lebensdauer; ;
- Verbesserte Antischaumeigenschaften, die das Risiko der Schaumbildung im Hydraulikkreislauf von Ventilen deutlich reduzieren;

Erfüllt Spezifikationen

SAE 15W-40 | API SL/CF |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	15.0
Density at 20˚C, kg/m³	887
Viscosity index	130
Alkalinity, mg KOH/g	8.3
Flash point in open crucible, ˚C	220
Pour point, ˚C	-31

Temperaturbereich

-28˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-029:2007. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.