YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



CVL SP

YUKO MGE-10A (ISO 15)

Hydrauliköl.

Beschreibung

Wird für Hydrauliksysteme von Schiffsmaschinen u nd mobilen Bodenfahrzeugen verwendet, die in einem weiten Temperaturbereich arbeiten.

Hergestellt aus hochwertigen Grundölen mit Additivpaket.

Containertypen

Canister 20L

Barrel 200L

Vorteile

- Gute Schmiereigenschaften, die für eine ausreichende Verschleißfestigkeit sorgen;
- Schaumbeständigkeit;
- Hohe Oxidationsstabilität, mechanische Stabilität;
- Kompatibel mit allen Gummidichtungen.

Erfüllt Spezifikationen

ISO 15 |

Typische Kennwerte

Kinematic viscosity at 50˚C, mm²/s	13,8
Density at 20˚C, kg/m³	880
Viscosity index	90
Sulphur content, %	0,32
Flash point in open crucible, ˚C	130
Pour point, ˚C	-42

Temperaturbereich

-40˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-041:2008. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.