Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



CVL SP

YUKO MGE-46 L (HM 46)

Hydraulisches Öl.

Beschreibung

Bestimmt für Hydrauliksysteme in der Landwirtschaft (hydrostatischer Antrieb) und anderen Maschinen, die u nter einem Druck von 35 MPa mit einer kurzfristigen Erhöhung auf b is zu 42 MPa arbeiten.
Hergestellt aus hochwertigen Grundölen mit Additivpaket.

Containertypen

Canister 20L

Barrel 200L

In bulk

Vorteile

- Gute Schmiereigenschaften, die für eine ausreichende Verschleißfestigkeit sorgen;
- Schaumbeständigkeit und Korrosionsschutz;
- Kompatibel mit den Dichtungen von Hydraulikantrieben;
- Die Hauptölart, die im Hydrauliksystem mobiler Maschinen verwendet wird.

Erfüllt Spezifikationen

ISO 46 | ISO HM |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	46.1
Density at 20˚C, kg/m³	879
Viscosity index	95
Acid index, mg KOH/g	0.8
Flash point in open crucible, ˚C	226
Pour point, ˚C	15

Temperaturbereich

-13˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-003:2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.