Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



YUKO MGE-46V (HM 46)

Universelles Ganzjahres-Getriebeöl

Beschreibung

Bestimmt für Hydrauliksysteme (hydrostatische Antriebe) von Landmaschinen u nd anderen Maschinen, die mit einem Druck u nter 35 MPa arbeiten, mit kurzem Anstieg b is zu 42 MPa.
Hergestellt aus hochwertigen Grundölen mit Additivpaket.

Containertypen

Canister 5L | OILBOX 20L | Tin bucket 20L | Canister 20L | Barrel 200L | In bulk

Vorteile

- Gute Verschleiß-, Schaum- und Korrosionsschutzeigenschaften;
- Ausgezeichnete Fließfähigkeit bei niedrigen Temperaturen;
- Nicht aggressiv zu den Dichtungsmaterialien von Hydraulikgetrieben;
- Es ist die Hauptart von Ölen, die in den Hydrauliksystemen mobiler Geräte verwendet werden.

Erfüllt Spezifikationen

ISO 46 | ISO HM |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	46.1
Density at 20˚C, kg/m³	875
Viscosity index	95
Acid index, mg KOH/g	0.8
Flash point in open crucible, ˚C	210
Pour point, ˚C	-32

Temperaturbereich

-30˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-003-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.