YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



PVL

YUKO MOTOMIX 2T

Mineralmotoröl für zwei Schlagmotoren.

Beschreibung

Bestimmt für Schmiersysteme von luftgekühlten Zweitaktmotoren moderner Motorräder, Motorräder, Motorräder, Motorsägen und anderer Maschinen. Wird als Komponente in einer Öl-Kraftstoff-Mischung in einem vom Maschinenhersteller empfohlenen Verhältnis verwendet. Die Standardeinspritzung variiert von 1:32 bis 1:50.

Containertypen

Canister 1L | Canister 20L | Barrel 200L | In bulk

Vorteile

- Bietet gute Schmier-, Verschleiß-, Korrosionsschutz- und Reinigungsmitteleigenschaften durch das Paket der aktiven Additive; ;
- Sorgen Sie für eine Kohlenstoffabscheidung aus der Brennkammer;
- Die Möglichkeit der ganzjährigen Nutzung;
- Bietet eine lange Lebensdauer der Zündkerze;
- Minimiert die Wartungskosten;

Erfüllt Spezifikationen

API TC | JASO FB |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	8.5
Density at 20˚C, kg/m³	890
Viscosity index	90
Alkalinity, mg KOH/g	0.85
Flash point in open crucible, ˚C	215
Pour point, ˚C	-25

Temperaturbereich

-20˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-016-2004 This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.