YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND

YUKO MR-7V (ISO 32)

Kühlmittelschmieröl.

Beschreibung

Zum Bohren, Drehen, Fräsen, Gewindeschneiden und Verzahnen, Ziehen. Auch in Automaten, zur Behandlung von Kohlenstoff- und Legierungsstählen sowie einigen schwer zu behandelnden Stählen und Legierungen.

Containertypen

Barrel 180kg

In bulk

Vorteile

- Ermöglicht eine Erhöhung der Schnittgeschwindigkeit um 15-30%;
- Verbessert die Haltbarkeit der Schneidwerkzeuge;
- Reduziert die Rauheit der bearbeiteten Oberflächen;
- Verbessert die sanitär-hygienischen Arbeitsbedingungen.

Erfüllt Spezifikationen

ISO 32 |

Typische Kennwerte

Kinematic viscosity at 50˚C, mm²/s	25
Density at 20˚C, kg/m³	890
Corrosive effect on metals	stands
Flash point, ˚C	205
Sulphur content, %	1,5

Temperaturbereich

˚C 0 ˚C ˚C

Produced according to TU U 23.2-31852954-035:2008. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.