Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



SP

YUKO MS-20P(CB 50)

Motorenöl für Schiffs-, Diesellokomotiven- und stationäre Dieselmotoren.

Beschreibung

Wird zur Schmierung von Schiffs-, Lokomotiv- und stationären Dieselmotoren vom Typ 12CHN 18/20 verwendet, die mit schwefelarmem Kraftstoff b etrieben werden.
Hergestellt aus mineralischen Grundölen mit Additiven.

Containertypen

Barrel 200L

In bulk

Vorteile

- Hervorragende Schmiereigenschaften bieten den erforderlichen Schutz für die Arbeitsflächen;
- Hohe thermische und thermisch-oxidative Stabilität;
- Charakterisiert durch Schaumbeständigkeit;
- Geringe Flüchtigkeit bei hohen Betriebstemperaturen.

Erfüllt Spezifikationen

SAE 50 | API CB |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	20.9
Density at 20˚C, kg/m³	890
Viscosity index	90
Alkalinity, mg KOH/g	2.2
Flash point in open crucible, ˚C	245
Pour point, ˚C	-18

Temperaturbereich

-16˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-006-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.