YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



CVL

YUKO NIGROL-L (GL-1, SAE 140)

Mineralisches Sommer-Getriebeöl ohne Zusatzstoffe.

Beschreibung

Wird im Sommer als Antriebsfluid in Getrieben, niedrig b elasteten Einheiten von Industrieanlagen, freiliegenden Getrieben, Planetengetrieben von Kränen, Baggern, Zahnradgetrieben u nd Getriebeeinheiten von Industrieanlagen, Traktoren, Land- und Straßenmaschinen, Baumaschinen eingesetzt.

Containertypen

Canister 1kg	Canister 5kg	Tin bucket 20L	Canister 20L	Barrel 200L	In bulk

Vorteile

Erfüllt Spezifikationen

SAE 140 | API GL-1 |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	28.5
Flash point in open crucible, ˚C	160
Pour point, ˚C	-5

Temperaturbereich

-3˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-010-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.