YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND SP

YUKO OSM-1 (ISO 5)

Schmierung der Kühlmittelflüssigkeit.

Beschreibung

Wird zum Honen, Polieren, "Feinstarbeiten" von Gusseisen, Kohlenstoff- und Legierungsstählen, Aluminiumpolieren verwendet.

Containertypen

Canister 17,5kg

Barrel 175kg

In bulk

Vorteile

- Hat eine gute Waschkraft;
- Beschleunigt die Entfernung der Gülle aus der Schneidezone;
- Erhöht die Verschleißfestigkeit von Diamantschleifwerkzeugen;
- Hat eine gute Filtrierbarkeit;
- Kompatibel mit Hydraulikölen

Erfüllt Spezifikationen

ISO 5 |

Typische Kennwerte

Kinematic viscosity at 50˚C, mm²/s	3.5
Density at 20˚C, kg/m³	850
Flash point, ˚C	78
Corrosive effect on metals	stands
Sulphur content, %	0,22

Temperaturbereich

˚C 0 ˚C ˚C

Produced according to TU U 23.2-31852954-022:2005. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.