YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



PVL

YUKO PRAKTIK 20W-50

Ganzjährig mineralisches, hochviskoses Motorenöl.

Beschreibung

Bestimmt für Benzin- und Dieselmotoren von Pkw, Transportern u nd leichten Nutzfahrzeugen gemäß den Herstelleranweisungen in gemäßigter u nd heißer Umgebung.

Hergestellt aus hochwertigen Grundölen u nd ausgewählten Additivpaketen, die einen einwandfreien Betrieb, insbesondere in heißer Umgebung u nd u nter hohen Belastungen, gewährleisten.

Containertypen

Canister 1L | Canister 4L | Canister 5L | Tin bucket 20L | Barrel 200L | In bulk

Vorteile

- Garantierter Motorschutz bei hohen Temperaturen;
- Hohe Viskosität über die gesamte Betriebszeit des Motoröls;
- Reduziert den Verschleiß und den Geräuschpegel;
- Enthält ein Rauchschutzmittel;
- Eine breite Palette von Verpackungen erfüllt die Anforderungen aller Geräte.

Erfüllt Spezifikationen

SAE 20W-50 | API SF/CC |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	18.1
Density at 20˚C, kg/m³	890
Viscosity index	120
Alkalinity, mg KOH/g	5.5
Flash point in open crucible, ˚C	225
Pour point, ˚C	-25

Temperaturbereich

-22˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-045:2010. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.