YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND

YUKO PS-28

Öl für Walzwerke.

Beschreibung

Bestimmt für Getriebe u nd hochbelastete Einheiten von Walzwerksmaschinen, für die Ausrüstung von Eisenhütten, Stahlwerken, Reifenwerken u nd anderen Anlagen u nd anderen Unternehmen, in denen Öle für Walzwerke verwendet werden. Hergestellt aus hochwertigen Grundölen mit Additiven.

Containertypen

Barrel 200L

In bulk

Vorteile

- Gewährleistet die Stabilität des aufrechterhaltenden Gegendrucks des Ölfilms;
- Hervorragende Schmiereigenschaften bieten den erforderlichen Schutz für die Arbeitsflächen;
- Eine gute thermisch-oxidative Stabilität ermöglicht es, das Öl in Kreislaufsystemen von Geräten über einen längeren Zeitraum zu verwenden.

Erfüllt Spezifikationen

ISO 460 |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	28.5
Density at 20˚C, kg/m³	892
Viscosity index	92
Acid index, mg KOH/g	0,005
Flash point in open crucible, ˚C	260
Pour point, ˚C	-10

Temperaturbereich

-8˚C 0 ˚C +45˚C

Produced according to GOST 12672-77. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.