YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



SP

YUKO Rope grease 39U

Spezielles Seilschmierfett.

Beschreibung

Zur Schmierung von Bohr- und Bergseilen, Hebe- und Transportseilen von Maschinenseilen, die über einen weiten Temperaturbereich von - 25°C b is + 50°C b etrieben werden.
Zum Schutz vor Korrosion u nd zur Verbesserung der Leistungsfähigkeit von Seilen (Reduzierung von Reibung u nd Verschleiß des Drahtseils während der Arbeit). Fettbasis sind Öle u nd feste Kohlenwasserstoffe.

Containertypen

Tin bucket 17,0kg

Barrel 170kg

Vorteile

- erhöht die Widerstandsfähigkeit der Seile gegen Reibung, Verformung und Bruch;
- Auswaschbeständigkeit;
- Korrosionsschutzeigenschaften;
- Speichern der Betriebseigenschaften in einem weiten Temperaturbereich;
- Verbesserte Anti-Reibungs- und Konservierungseigenschaften.

Erfüllt Spezifikationen

Typische Kennwerte

Dropping point, °C,	68
Funnel viscosity at 100°C	6
Thermal stability at 100°C:	
- volatility, %	0,2
Low temperature properties:	
- at minus 25°C	stands

Temperaturbereich

-25˚C 0 ˚C +50˚C

Produced according to TU U 20.5-31852954-077:2016. This information is reference and it can be changed without a notice. This article is from 01/09/2016, it replaces all the early published descriptions of the product.