YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND SP

YUKO SHAHTOL-UT

Spezial-Getriebefett

Beschreibung

Wälzgetriebefett für die Untertageausrüstung von Kohlebergwerken, Getriebe von Bergbaugeräten, Getriebe von landwirtschaftlichen Geräten, leichte u nd mittelschwere Geräte von Industrieanlagen: freiliegende Getriebe u nd Getriebe.

Hergestellt durch Verdickung von Erdöl mit oxidierten Vaseline-Säuren Kalziumseife u nter Zusatz von Verschleißschutz u nd extremen Druckzusätzen.

Containertypen

Tin bucket 17,0kg

Barrel 170kg

Vorteile

- Gute Wasserbeständigkeit;
- Optimaler Verschleißschutz und extreme Druckeigenschaften;
- Ausreichende mechanische Stabilität.

Erfüllt Spezifikationen

Meets the requirements of the mining industry. |

Typische Kennwerte

Appearance	Homogeneous black grease
Kinematic viscosity at 100°C, mm²/s	20
Flash point, °C, ьшт	195
Corrosive effect on metals	stands
Tribological characteristics on four-ball tester at temp. (20±5°C).	
- welding load, N	3600
- critical load, N	980
- scuff index, N	600

Temperaturbereich

-10˚C 0 ˚C +110˚C

Produced according to TU U 23.2-31852954-056:2013. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.