YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



YUKO Solidol Extra

Universelles Fett auf Kalziumbasis.

Beschreibung

Wird zur Schmierung von Grobreibungseinheiten in Maschinen u nd Anlagen von Fahrzeugen, landwirtschaftlichen Geräten, Hand- und anderen Werkzeugen, Schrauben- und Kettenantrieben, Getrieben mit niedriger Drehzahl u sw. verwendet. Temperaturbereich: -25°C . . . . . +65°C.

Hergestellt aus mittelviskosen reinen Grundölen, verdickt mit hydratisierten Fettsäuren Kalziumseife.

Containertypen

Doypack 0,150kg	Doypack 0,375kg	Tin 400g	Tin 800g	Plastic pail 4,5kg	Plastic pail 9kg	OILBOX 17,0kg	Tin bucket 17,0kg	Barrel 170kg

Vorteile

- Hat hervorragende Viskositäts-Temperatur-Eigenschaften;
- Weniger Verdichtung während der Lagerung;
- Hohe kolloidale, chemische und mechanische Stabilität;
- Guter Verschleißschutz und extreme Druckeigenschaften;
- Vielfalt an Verpackungsarten, Packungsvolumen;
- Entspricht GOST.

Erfüllt Spezifikationen

NLGI 3 |

Typische Kennwerte

Dropping point, ˚C	95
Penetration at 25˚C, mm×10^{-1}	260
Tensile strength at 50˚C, Pa	450

Temperaturbereich

-30˚C 0 ˚C +65˚C

Produced according to GOST 1033-79. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.