

YUKO Solidol Extra

Universelles Fett auf Kalziumbasis.



Beschreibung

Wird zur Schmierung von Grobreibungseinheiten in Maschinen und Anlagen von Fahrzeugen, landwirtschaftlichen Geräten, Hand- und anderen Werkzeugen, Schrauben- und Kettenantrieben, Getrieben mit niedriger Drehzahl usw. verwendet. Temperaturbereich: -25°C +65°C.

Hergestellt aus mittelviskosen reinen Grundölen, verdickt mit hydratisierten Fettsäuren Kalziumseife.

Containertypen

 Doypack	 Doypack	 Tin	 Tin	 Plastic pail	 Plastic pail	 OILBOX	 Tin bucket	 Barrel
0,150kg	0,375kg	400g	800g	4,5kg	9kg	17,0kg	17,0kg	170kg

Vorteile

- Hat hervorragende Viskositäts-Temperatur-Eigenschaften;
- Weniger Verdichtung während der Lagerung;
- Hohe kolloidale, chemische und mechanische Stabilität;
- Guter Verschleißschutz und extreme Druckeigenschaften;
- Vielfalt an Verpackungsarten, Packungsvolumen;
- Entspricht GOST.

Erfüllt Spezifikationen

NLGI 3 |

Typische Kennwerte

Dropping point, °C	95
Penetration at 25°C, mm×10 ⁻¹	260
Tensile strength at 50°C, Pa	450

Temperaturbereich



Produced according to GOST 1033-79. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.