YUKO.UA

# Produktdatenblat
# Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com




CVL

# YUKO SUPER DIESEL 20W-50

## Mehrbereichs-Motorenöl mit hoher Viskosität.

## Beschreibung

Mehrbereichsmotorenöl YUKO SUPER DIESEL 20W50 für Dieselmotoren ( turboaufgeladen oder nicht) und Benzinmotoren, die die Einhaltung der API CF-4/SG-Normen erfordern.

Aufgrund der hohen Viskosität nehmen die Dichtheit u nd Verdichtung des Motors zu. Additivpaket b ietet Schutz vor Schmutz, Abnutzung u nd Korrosion

## Containertypen

Canister 20L

Barrel 200L

## Vorteile

- Hervorragende Reinigungs- und Korrosionsschutzeigenschaften;
- Stabile Viskosität bei hohen Betriebstemperaturen;
- Durch die Einhaltung der API ist CF-4 - optimal für die am häufigsten verwendeten Motoren geeignet;
- Kompatibel mit Dichtungen.

## Erfüllt Spezifikationen

**SAE 20W-50 | API CF-4/SG |**

## Typische Kennwerte

| | |
|---|---|
| Kinematic viscosity at 100˚C, mm²/s | 16,5 |
| Density at 20˚C, kg/m³ | 910 |
| Viscosity index | 120 |
| Alkalinity, mg KOH/g | 7,0 |
| Flash point in open crucible, ˚C | 210 |
| Pour point, ˚C | -30 |

**Temperaturbereich**

-27˚C 0 ˚C +45˚C

Produced according to 23.2-31852954-029:2007. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.